



Features

- Long-throw woofer for high power handling
- High quality crossover components
- Extended frequency response
- Swivel, die-cast aluminium front baffle
- Boundary compensation fitted
- Die-cast woofer chassis
- Fully magnetically shielded
- Alloy cones for detail and clarity
- IR sensor fixing

Complete with manual, cut-out guide template, paint cover, grille and removable badge/logo.

Specifications

HF Unit - 25mm Neodymium Tweeter, ferrofluid cooled. Magnetically shielded

LF Units - 2x110mm drivers with 32mm long throw voice coils. Lightweight alloy cones

Power Handling - 175 Watts RMS

Frequency Response - 50Hz - 23kHz

Sensitivity - 87dB

Impedance - 8 Ohms

4mm Gold-plated Spring lock terminals

Dimensions & Weight

250 x 416mm (WxH) Overall size

210 x 370mm Hole Cut-out (WxH)

102mm Clearance Depth

5kg Weight

AELITE_{255Ci}
CUSTOM INSTALL SERIES

For more information please contact:

Acoustic Energy Limited, 16 Bridge Road, Gloucestershire, England GL7 1NJ
Tel - 01285 654432 / Fax - 01285 654430 Email - uksales@acoustic-energy.co.uk



AELITE 255Ci
CUSTOM INSTALL SERIES



Acoustic Energy presents the AELITE Custom Install Series. Our flagship range of In-wall and In-ceiling loudspeakers.

Designed to combine the best in high end high-fidelity audio with ease of installation and unequalled value.

All AELITE Ci Series loudspeakers are pre-primed with a white ready-to-paint finish. Standard "dog leg" fixings and cut-out guides are also included.

