

EXTREME5 EXTREME8




AE's expertise in hi-fidelity loudspeaker design comes to the garden, pool, decking, house or gym with the all-new Extreme loudspeaker range.

The Extreme Series are fully water resistant loudspeakers capable of withstanding dust, dirt, humidity, severe temperature changes and extremes of weather.

The high quality industrial spec connectors (supplied) further improve durability and make the Extreme range ideal for use both outdoors and in challenging interior environments such as pubs, clubs, kitchens and bathrooms.





Specifications	Extreme 5	Extreme 8
Type	2-way, closed-box loaded	2-way, closed-box loaded.
LF/MF Driver	110mm pressed alloy cone	160mm pressed alloy cone.
HF Driver	25mm Dome	25mm Dome.
Filter Network	3rd order at 3.0kHz	3rd order 3.0kHz
Cabinet	Reinforced Structural Polymer	Reinforced Structural Polymer.
Frequency Response	70Hz to 18kHz ± 3 dB	55Hz to 18kHz ± 3 dB
Frequency Range	60Hz to 20kHz @ -6dB	45Hz to 20kHz @ -6dB
Power Handling	125W peak programme	150W peak programme
Amplifier Compatibility	25 - 125 Watts into 8 Ohms	25 - 150 Watts into 8 Ohms
Nominal Impedance:	8 Ohms	8 Ohms
Sensitivity	89dB for 1 Watt at 1 metre	90dB for 1 Watt at 1 metre
Enclosure Sealing Specification	IP54	IP54

Extreme Series speakers are fitted with 2-pole Neutrik Speakon connection sockets. An appropriate Speakon plug is included in each pack. Speakon sockets and plugs provide a reliable, secure, and potentially weather-proof connection.

Dimensions, Weight & Finish	Extreme 5	Extreme 8
Dimensions (H x W x D)	260 x 160 x 180mm	390 x 260 x 260mm
Weight (including bracket)	3.0kg (single, unpacked)	7.0kg (single, unpacked)
Finish	Black or white	Black or white

EXTREME5 EXTREME8

For more information please contact:

Acoustic Energy Limited, 16 Bridge Road, Gloucestershire, England GL7 1NJ
Tel - 01285 654432 / Fax - 01285 654430 Email - uksales@acoustic-energy.co.uk

