

ADVANCED
INFORMATION
AE ACTIVE



The new AE Active loudspeaker is an evolved version of our highly successful AE1 Active, first launched in 2017. Refreshed, updated and upgraded for 2026... acoustically and aesthetically.

While the new AE Active retains its fully analogue design philosophy - including a linear power supply, Class A/B amplification and analogue line-level crossover filters and EQ - it benefits from several meaningful improvements.

We've refined the power amplifiers to deliver greater dynamic capability, and reworked the analogue filters to minimise phase loss, resulting in a more immediate and expressive sound. Responding to customer feedback, we've added a selectable low-power standby mode with auto signal sensing for improved energy efficiency and seamless system integration. The rear panel also features an upgraded RCA input for improved compatibility with premium audiophile interconnects.

Acoustically, the AE Active now uses the mid-bass woofer developed for our award-winning AE1 40th Anniversary Edition. We've also introduced a new rear chamber for the tweeter, significantly reducing distortion around the crossover region. This also reduces harshness and delivers a more natural, lifelike vocal range.

ACOUSTIC-ENERGY.CO.UK



Externally, the cabinet has been subtly reshaped and fitted with a new silicone-finished driver trim for a cleaner, more refined appearance. Finish options are **high-gloss black**, **high-gloss white** and a **new natural walnut wood veneer**.

Designed for versatility, the AE Active is a perfect partner for both analogue and digital hi-fi systems, as well as home studios and high-quality desktop monitoring setups.

AE ACTIVE Specifications

- Bandwidth: 42Hz-28kHz
- Amplifier: Class A/B with linear power supply
- Amplifier power: LF: 50W / HF: 50W
- Crossover: 3.1kHz 2nd order
- Woofer: 125mm chassis with Alu/Ceramic cone
- Tweeter: 27mm Alu dome with WDT waveguide
- Cabinet: 18mm MDF with bracing and damping panels
- Inputs: RCA and Balanced XLR
- Controls: Volume adjust 0dB to -inf (HF shelf +/-2dB / LF shelf +/-2dB)
- Power connection: IEC C13
- Auto power on: 24mV
- Auto power on/off: 15 minutes
- Voltage selection: Manual switching
- Grilles: Slim, cloth magnetic fit
- Dimensions: 312 x 180 x 250 (HxWxD)
- Weight: 7.5kg (each)
- Finishes: Walnut Wood Veneer, High Gloss Black and High Gloss White